



ANTICALC

GCV 50 44 16D B14 TBR



Model	Anticalc 50
Real Volume	50 L
Rated power	1600/800 W
Heating time Δt 45K (15 - 60°C)**80°C	1:37/3:15 h:min
Annual consumption of electricity AEC	1392 kWh
Energy class	C
Height	0.608 m
Width	0.440 m
Depth	0.468 m
Diameter	440 mm



Mounting	Vertical
Load profile	M
V40	74 L
T _{out of the box}	60 °C
MAX40	88 L



The vertical electric water heaters of the Anticalc series have been developed for trouble-free, long-term and reliable operation in areas supplied with hard and highly mineralized and/or aggressive water. The Anticalc heating element works at low surface temperature, which limits the deposition of lime scale. The range offers models with storage capacity of 50 to 100 litres.

- INSUTECH - an in-house TESY technology for highly efficient insulation and extremely low heat losses
- PISTON EFFECT for supervision of the speed of incoming water and increase of the hot water amount with up to 15%
- Option for choosing between two degrees of electric power
- ECO position of the external regulator for cost efficient and prolonged operation
- 3 light indicators for recognition of the work modes
- Freeze protection
- Glass-ceramic coating for corrosion protection
- Plasma-arc welding of the water tank for extended useful life