


Ključ nasadni imbus, prihvat 1/2"

192/2HX






Profili



Atributi proizvoda

- materijal: glava: Premium Flex Plus ugljični čelik, kromirana
- materijal: vrh: Premium Plus specijalni alatni čelik, nauljeno protiv korozije
- u cijelosti ojačan i zakaljen
- dimenzije 17, 19, 22 i 24 mm se koriste kod montaže prednjeg kotača
- izrađeni prema standardu DIN 7422 (samo metričke dimenzije)



		D	L	L1	
600978	4	23	60	24	60
603420	5	23	60	24	60

		D	L	L1	
603421	6	23	60	24	60
603422	7	23	60	24	75
603423	8	23	60	24	81
605923	9	23	60	24	85
603424	10	23	60	24	95
603425	12	23	60	24	116
624033	13	23	60	24	100
603426	14	23	60	24	168
624034	15	23	60	24	115
603427	17	24	60	20	187
603428	19	26.5	60	20	195
623141	22	26,5	60	20	196
623142	24	26,5	60	20	210
619894	3/16"	22.9	40	24	60
619895	7/32"	22.9	40	24	60
619896	1/4"	22.9	40	24	60
619899	3/8"	22.9	40	24	95
619900	1/2"	22.9	40	24	116
619901	9/16"	22.9	40	24	168
619902	5/8"	22.9	40	24	187
619904	3/4"	26.8	40	21	195

* Slike proizvoda su simbolične. Sve dimenzije su u mm, masa je u g.

upotreba (pictures)

